

**RECOVERY/FISHING RODS**



SIZE	LENGTH	THD	O.D.	I.D.	T.P.I	WEIGHT KGS	PART NUMBERS
BW	1.5	LH	54	38	3	15.1	K10-02-003
BW	3	LH	54	38	3	28.7	K10-02-004
NW	1.5	LH	66.7	51	3	19.0	K10-03-003
NW	3	LH	66.7	51	3	36.0	K10-03-004

ALL KUVAWALA RECOVERY RODS ARE LEFT HAND THREADED AND MANUFACTURED FROM THE HIGHEST QUALITY RAW MATERIALS i.e. COLD DRAWN SEAMLESS TUBES OF GRADE SAE 1541 . THESE HAVE EXTREMELY HIGH MECHANICAL PROPERTIES AND STRAIGHTNESS BETTER THAN 1 : 4000 . ALL DRILL RODS ARE PARALLEL WALL.

STANDARD ' W ' SERIES DRILL RODS ARE LEFT HAND THREADED AND FLUSH COUPLED AND A COUPLING IS SUPPLIED WITH EACH ROD LENGTH. COUPLINGS ARE MADE OF HEAT TREATED ALLOY STEEL.

WEIGHTS GIVEN ABOVE ARE INCLUSIVE OF COUPLING WEIGHT.