


WIRELINE INDUCTION HARDENED DRILL ROD



ROD ENDS ARE HARDENED (30 TO 35 Rc) THROUGHOUT THE WALL THICKNESS UPTO A LENGTH OF 150MM

SIZE	LENGTH	O.D.	I.D.	T.P.I	WEIGHT KGS	PART NUMBERS
AWL	1.5M	44.5	34.9	4	7.1	K3-01-001
AWL	3.0M	44.5	34.9	4	14.2	K3-01-002
AT	1.5M	44.5	34.9	2.5	7.1	K3-01-003
AT	3.0M	44.5	34.9	2.5	14.2	K3-01-004
ARWL	1.5M	44.5	34.9	4	7.1	K3-01-005
ARWL	3.0M	44.5	34.9	4	14.2	K3-01-006
BWL	1.5M	55.6	46	3	9.4	K3-02-001
BWL	3.0M	55.6	46	3	18.6	K3-02-002
BT	1.5M	55.6	46	2.5	9.4	K3-02-003
BT	3.0M	55.6	46	2.5	18.6	K3-02-004
BRWL	1.5M	55.6	46	3	9.4	K3-02-005
BRWL	3.0M	55.6	46	3	18.6	K3-02-006
NWL	1.5M	69.9	60.3	3	12	K3-03-001
NWL	3.0M	69.9	60.3	3	23.5	K3-03-002
NT	1.5M	69.9	60.3	2	12.1	K3-03-003
NT	3.0M	69.9	60.3	2	23.6	K3-03-004
NRWL	1.5M	69.9	60.3	3	12	K3-03-005
NRWL	3.0M	69.9	60.3	3	23.5	K3-03-006
HWL	1.5M	88.9	77.8	3	18	K3-04-001
HWL	3.0M	88.9	77.8	3	34.9	K3-04-002
HT	1.5M	88.9	77.8	2	18.2	K3-04-003
HT	3.0M	88.9	77.8	2	35.2	K3-04-004
HRWL	1.5M	88.9	77.8	3	18	K3-04-005
HRWL	3.0M	88.9	77.8	3	34.9	K3-04-006
PHD	1.5M	114.3	101.6	2.5	28.2	K3-05-003
PHD	3.0M	114.3	101.6	2.5	53	K3-05-004

ALL KUVAWALA WIRELINE DRILL RODS ARE MANUFACTURED FROM THE HIGHEST QUALITY RAW MATERIALS i.e. COLD DRAWN SEAMLESS TUBES OF GRADE SAE 1541 / SAE 4130 . THESE HAVE EXTREMELY HIGH MECHANICAL PROPERTIES FOR MID BODY AND STRAIGHTNESS BETTER THAN 1 : 6000 .